

NP 129E

New Modular Industrial Patch Panel

Belden® introduces the MIPP™, a modular industrial patch panel that makes it possible to terminate fiber and copper in one solution.



The New MIPP™ Brings Flexibility and Versatility to Cable Termination, Providing Space and Cost Savings as well as Maximum System Availability.

BELDEN



HIRSCHMANN

A **BELDEN** BRAND

- Combining copper and fiber management for the first time in one patch panel for maximum system flexibility and versatility
- The innovative modular design enables quick and easy installation significantly reducing initial set-up costs

The new MIPP™ is a termination panel for cables that need to be connected to active equipment such as switches. Thanks to the modular design, MIPP™ can be linked to create a large single patch panel, to which, for the first time ever, both fiber and copper cables can be connected.

The MIPP™ is a completely new solution that provides the ideal connection between Belden® cables and Hirschmann™ switches. Available in a choice of modules suitable for both fiber and copper cables, up to 6 modules can be connected to create a single panel that can accommodate both types of cable at the same time for maximum system flexibility. Using patchcords to connect to active equipment, cables can be terminated outside the cabinet in an organised and structured manner to ensure the highest level of reliability.

Applications

The MIPP™ is ideal for use in a wide range of industrial applications requiring maximum system reliability and flexibility. The industrial design makes it highly suited for use in Machine Building, Transportation, Alternative Power Generation, Power Transmission & Distribution, and Oil & Gas markets, as well as more general use in enterprise, buildings and other applications.

Benefits

The MIPP™ is designed for industrial use, where its functionality and reliability can make a significant contribution to the uptime and availability of the system. Thanks to its modular design, installation is quick and easy, saving time and significantly reducing initial set-up costs, whilst at the same time contributing to greater reliability and easier and more efficient system management, requiring less maintenance.

Designed to have the same look and feel as the Hirschmann™ range of industrial switches, the MIPP™ has a lightweight aluminium structure which increases its overall versatility. It can easily be mounted on a DIN Rail, or it can even be attached at the sides of the cabinets simply using a wall mount plate. Thanks to its small housing, high port density and modularity, cabinet space is kept to a minimum.

**A new product to serve your needs.
Be certain.**

MIPP™: A Versatile, Modular Patch Panel for Industrial Use



MIPP™ is a modular, flexible patch panel that combines both copper and fiber cabling in one innovative solution.

The MIPP™ is available as both single and double modules:

- Single Fiber Modules (up to 12 fiber connections)
 - 6 x SC duplex adapters
 - 6 x LC duplex adapters
 - 6 x ST duplex adapters
 - 6 x E-2000™ duplex adapters
- Single Copper Modules
 - 4 x RJ45 keystone shielded
 - 4 x RJ45 keystone unshielded
 - 4 x RJ45 coupler shielded
 - 4 x RJ45 coupler unshielded
- Double Fiber Modules (up to 24 fiber connections)
 - 12 x SC duplex adapters
 - 12 x LC duplex adapters
 - 12 x ST duplex adapters
 - 12 x E-2000™ duplex adapters







Thanks to their compact dimensions, up to 6 modules can be combined in any permutation – and when required, each module can be easily removed or replaced for maximum flexibility.

The Advantages at a Glance

- Accommodating various media and connectors
- LC, SC, ST and E-2000™ fiber duplex adapters

- RJ45 copper keystone jacks (Shielded and Unshielded, Cat 5e, Cat 6, Cat 6A)
- RJ45 copper coupler (Shielded and Unshielded, Cat 6A)
- High port density for maximum use of available space
- Easy to use, allows space for handling cable and module is removable from unit to facilitate connection/splicing
- Splice tray and multiple fingers for easy fiber management
- Cable entries in two places (top or bottom), for ease of use and choice of placement in cabinet
- Three cable entries for single fiber module, for ring topology applications
- Double fiber module accommodates hybrid fiber cables, with single mode and multi mode fibers
- Resilient for protection against the harsher industrial environments
- Wide temperature range from -20°C to +70°C
- Available as part of a system with market leading Hirschmann™ switches and high performance Belden cabling for optimum reliability in Industrial Ethernet networks
- UL approval (UL 1863)

Technical Information

| Housing Type and Description | | | | | | |
|--|---|---|---|--|---|---|
| Description | Modular Industrial Patch Panel, DIN Rail | | | | | |
| Number of Single Modules | 1 | 2 | 3 | 4 | 5 | 6 |
| |  |  |  |  |  |  |
| Mechanical Construction | | | | | | |
| Material Housing | Aluminium | | | | | |
| Dimensions (W x H x D) | 42 x 138 x 122 mm | 72 x 138 x 122 mm | 102 x 138 x 122 mm | 132 x 138 x 122 mm | 162 x 138 x 122 mm | 192 x 138 x 122 mm |
| Dimensions with Adapters and Gland, max. (H x D) | 165 x 133 mm | 165 x 133 mm | 165 x 133 mm | 165 x 133 mm | 165 x 133 mm | 165 x 133 mm |
| Mounting | DIN Rail | | | | | |
| Appr. Weight Housing | 360 g | 530 g | 697 g | 865 g | 1034 g | 1200 g |
| Dimension Wallmount Plate (W x H) | 38 x 157 mm | 68 x 157 mm | 98 x 157 mm | 128 x 157 mm | 158 x 157 mm | 188 x 157 mm |
| Appr. Weight Wallmount Plate | 67 g | 119 g | 172 g | 223 g | 277 g | 329 g |



| Module Type and Description | | | | | | |
|-----------------------------|--|--|--|--|--|---|
| Type | Single Module | Single Module | Single Module | Single Module | Single Module | Single Module |
| Description | 6 x SC Duplex | 6 x LC Duplex | 6 x ST Duplex | 6 x E-2000™ Duplex | 4 x RJ45 Keystone Jack, Unshielded | 4 x RJ45 Coupler, Unshielded |
| | | | | | | |
| Mechanical Construction | | | | | | |
| Material | Steel | | | | | |
| Adapter/Keystone Types | <ul style="list-style-type: none"> Blue SC adapter OS2 UPC zirconia ceramic Beige SC adapter OM1/OM2 PC phosphor bronze Aqua SC adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Blue LC adapter OS2 UPC zirconia ceramic Beige LC adapter OM1/OM2 PC phosphor bronze Aqua LC adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Blue ST adapter OS2 UPC zirconia ceramic Beige ST adapter OM1/OM2 PC phosphor bronze Aqua ST adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Blue E-2000™ adapter OS2 UPC zirconia ceramic Beige E-2000™ adapter OM1/OM2 PC zirconia ceramic Aqua E-2000™ adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Cat 5e Modular Jack, Keyconnect AX101310, black Cat 6+ Modular Jack, Keyconnect AX101321, black Cat 6A/10GX Modular Jack, Keyconnect AX102283, black | <ul style="list-style-type: none"> Cat 6A/10GX Modular Jack, Keyconnect Couple AX104024, black |
| Appr. Weight Module | 218 g | 218 g | 218 g | 218 g | 516 g | 516 g |
| Protection Class | IP40 | IP40 | IP40 | IP40 | IP20 | IP20 |
| Cable Entry | 3, M16 Gland | 3, M16 Gland | 3, M16 Gland | 3, M16 Gland | – | – |
| Maximum Diameter Cable | 10 mm | 10 mm | 10 mm | 10 mm | 4 x 7.5 mm | 4 x 7.5 mm |
| Cable Types | Fiber cables up to 12 fibers: loose tube, mini-breakout, breakout cables | | | | Cat 5e unshielded, Cat 6 unshielded, Cat 6A unshielded | |

| Module Type and Description | | | | | | |
|-----------------------------|--|--|--|---|--|--|
| Type | Double Modules | Double Modules | Double Modules | Double Modules | Single Module | Single Module |
| Description | 12 x SC Duplex | 12 x LC Duplex | 12 x ST Duplex | 12 x E-2000™ Duplex | 4 x RJ45 Keystone Jack, Shielded | 4 x RJ45 Coupler, Shielded |
| | | | | | | |
| Mechanical Construction | | | | | | |
| Material | Steel | | | | | |
| Adapter/Keystone Types | <ul style="list-style-type: none"> Blue SC adapter OS2 UPC zirconia ceramic Beige SC adapter OM1/OM2 PC phosphor bronze Aqua SC adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Blue LC adapter OS2 UPC zirconia ceramic Beige LC adapter OM1/OM2 PC phosphor bronze Aqua LC adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Blue ST adapter OS2 UPC zirconia ceramic Beige ST adapter OM1/OM2 PC phosphor bronze Aqua ST adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Blue E-2000™ adapter OS2 UPC zirconia ceramic Beige E-2000™ adapter OM1/OM2 PC phosphor bronze Aqua E-2000™ adapter OM3/OM4 PC zirconia ceramic | <ul style="list-style-type: none"> Cat 5e Shielded Modular Jack, Keyconnect AX104595, metal body Cat 6+ Shielded Modular Jack, Keyconnect AX104596, metal body Cat 6A/10GX Shielded Modular Jack, Keyconnect AX104562, metal body | <ul style="list-style-type: none"> Cat 6A/10GX Shielded Modular Jack, Keyconnect Coupler AX104501, metal body |
| Appr. Weight Module | 450 g | 450 g | 450 g | 450 g | 636 g | 636 g |
| Protection Class | IP40 | IP40 | IP40 | IP40 | IP20 | IP20 |
| Cable Entry | 1, M20 Gland | 1, M20 Gland | 1, M20 Gland | 1, M20 Gland | – | – |
| Maximum Diameter Cable | 13 mm | 13 mm | 13 mm | 13 mm | 4 x 7.5 mm | 4 x 7.5 mm |
| Cable Types | Fiber cables up to 24 fibers: loose tube, mini-breakout Hybrid Fiber cable: 6 x SM + 6 x OM1, 6 x SM + 6 x OM2, 6 x SM + 6 x OM3, 6 x SM + 6 x OM4 | | | | Cat 5e shielded, Cat 6 shielded, Cat 6A shielded, Cat 7 shielded | |

| Accessories | | | | | | |
|--|--|---|--|---|--|--|
| Pigtails (1 pack of 12 pigtails, 900 micron, 0.6 m in 12 different colours) | <ul style="list-style-type: none"> SC/UPC SM 9/125, OS2 SC/PC MM 62.5/125, OM1 SC/PC MM 50/125, OM2 SC/PC MM 50/125, OM3 SC/PC MM 50/125, OM4 | <ul style="list-style-type: none"> LC/UPC SM 9/125, OS2 LC/PC MM 62.5/125, OM1 LC/PC MM 50/125, OM2 LC/PC MM 50/125, OM3 LC/PC MM 50/125, OM4 | <ul style="list-style-type: none"> ST/UPC SM 9/125, OS2 ST/PC MM 62.5/125, OM1 ST/PC MM 50/125, OM2 ST/PC MM 50/125, OM3 ST/PC MM 50/125, OM4 | <ul style="list-style-type: none"> E-2000™/UPC SM 9/125, OS2 E-2000™/PC MM 62.5/125, OM1 E-2000™/PC MM 50/125, OM2 E-2000™/PC MM 50/125, OM3 E-2000™/PC MM 50/125, OM4 | | |
| Brilliance Field Installable Connector (900 micron) | 12 brilliance connectors SC: <ul style="list-style-type: none"> SM 9/125, OS2, blue, AX104247 MM 62.5/125, OM1, beige, AX104244 MM 50/125, OM2, black, AX104245 MM 50/125, OM3/OM4, aqua, AX104246 | 12 brilliance connectors LC: <ul style="list-style-type: none"> SM 9/125, OS2, blue, AX104243 MM 62.5 micron, OM1, beige, AX104240 MM 50 micron, OM2, black, AX104241 MM 50 micron, OM3/OM4, aqua, AX104242 | 24 brilliance connectors ST: <ul style="list-style-type: none"> SM 9/125, OS2, blue, AX104251 MM 62.5/125, OM1, beige, AX104248 MM 50/125, OM2, black, AX104249 MM 50/125, OM3/OM4, aqua, AX104250 | | | |

MIPP Product Configurator

Use the configured product code to order:

M I P P / J D / 1 L 1 P / 2 T 9 N / X X X X / X X X X / X X X X / X X X X / X X

MODULE 1 MODULE 2 MODULE 3 MODULE 4 MODULE 5 MODULE 6

Design/Model

MIPP = Modular Industrial Patch Panel

Housing Type (Note: A double module requires two places)

- | | |
|-----------------------------|----------------------------------|
| X = No Housing | H = 2 x Double module fiber |
| A = 1 x Single module | I = 3 x Double module fiber |
| B = 2 x Single module | J = 1 x SM + 1 x DM fiber |
| C = 3 x Single module | K = 1 x SM + 2 x DM fiber |
| D = 4 x Single module | L = 2 x SM + 1 x DM fiber |
| E = 5 x Single module | M = 2 x SM + 2 x DM fiber |
| F = 6 x Single module | N = 3 x SM + 1 x DM fiber |
| G = 1 x Double module fiber | O = 4 x SM + 1 x DM fiber |

Note: SM = Single module and DM = Double module

Mounting Type

- X = No Housing
 W = Wall Mount Plate included
D = Standard DIN Rail

Module Type

- 1** = Single module (fiber or blind)
 2 = Double module (fiber or blind)
 C = Single copper module

Adapter and Keystone Type

- | | |
|-------------------------------------|--------------------------|
| T = ST/ST Duplex adapters | d = Shielded couplers |
| L = LC/LC Duplex adapters | u = Unshielded keystones |
| S = SC/SC Duplex adapters | s = Shielded keystones |
| E = E-2000™/E-2000™ Duplex adapters | N = Blind module |
| c = Unshielded couplers | |

Fiber Type/Category Type for Copper

- | | |
|-------------------------|-------------------------|
| 1 = MM/OM1 | 8 = 6 x SM/OS2, 6 x OM4 |
| 2 = MM/OM2 | 9 = SM/OS2 |
| 3 = MM/OM3 | e = Cat 5e |
| 4 = MM/OM4 | d = Cat 6 |
| 5 = 6 x SM/OS2, 6 x OM1 | a = Cat 6A |
| 6 = 6 x SM/OS2, 6 x OM2 | N = Blind module |
| 7 = 6 x SM/OS2, 6 x OM3 | |

Accessories and Number of Keystones/Couplers

- P** = Pigtailed
 B = Brilliance Field Installable connectors
 2 = 2 keystones/couplers
 4 = 4 keystones/couplers
 N = No accessories

Description of Parts Configured

Panel with one single module and one double module fiber:

- OM1 single fiber module (three input version) with 6 LC duplex adapters including pack of 12 pigtailed
- SM/OS2 double fiber module with 12 ST duplex adapters

Always Stay Ahead with Belden

In a highly competitive environment, it is crucial to have reliable partners who are able to add value to your business. When it comes to signal transmissions, Belden is the number one solutions provider. We understand your business and want to know your specific challenges and targets to see how effective signal transmission solutions can push you ahead of the competition. By combining the strengths of our three leading brands, Belden®, Hirschmann™; and Lumberg Automation™, we are able to offer the solution you need. Today it may be a single cable, a switch or a connector, thus solving a specific issue; tomorrow it can be a complex range of integrated applications, systems and solutions.

We guarantee the superior performance of your mission-critical systems, even in the most demanding circumstances. If signal transmission is vital to your business, get in touch with the partner that delivers. Be certain. Belden.