

# CERTIFICATE

## (1) Type Examination

(2) **Product intended for use in potentially explosive atmospheres - Directive 2014/34/EU**

(3) Type Examination Certificate Number: **DEKRA 17ATEX0024 X** Issue Number: **1**

(4) Product: **Industrial Ethernet Switch 19" GRS 1X4X Series, Power Supply Unit Series and Media Modules GMM Series**

(5) Manufacturer: **Hirschmann Automation and Control GmbH**

(6) Address: **Stuttgarter Strasse 45-51, 72654 Neckartenzlingen, Germany**

(7) This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

(8) DEKRA Certification B.V., certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014.

The examination and test results are recorded in confidential test report no. 219865100, Issue 1.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0 : 2012 + A11 : 2013**

**EN 60079-15 : 2010**

except in respect of those requirements listed at item 18 of the Schedule.

(10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.

(11) This Type Examination Certificate relates only to the design and construction of the specified product and not to the manufacturing process and its monitoring.

(12) The marking of the product shall include the following:



**II 3 G**

**Ex nA IIC T4 Gc**

Date of certification: **28 March 2018**

DEKRA Certification B.V.

**R. Schuller**  
Certification Manager

(13) **SCHEDULE**

(14) **to Type Examination Certificate DEKRA 17ATEX0024 X**

Issue No. 1

(15) **Description**

The Industrial Ethernet Switch 19" GRS 1X4X Series, Power Supply Unit Series and Media Modules GMM Series for 19" mounting and intended for use in industrial automation applications, communicate via electrical or optical interfaces.

Ambient temperature range: 0 °C to +60 °C for Temperature range parameter "C" and "S"  
-40 °C to +70 °C for Temperature range parameters "T" and "E"

**Electrical data**

Supply: 24 ... 48 Vdc, 2,0 ... 1,0 A (identification mark L) or  
48 ... 54 Vdc, 4,8 ... 4,2 A (identification mark L)

Relay output: max. 60 Vdc, max. 1 A (resistive load)

**Installation instructions**

The instructions provided with the product shall be followed in detail to assure safe operation.

(16) **Report Number**

No. 219865100, Issue 1.

(17) **Specific conditions of use**

1. The modules shall be installed in a suitable enclosure providing a degree of protection of at least IP54 according to EN 60079-15, taking into account the environmental conditions under which the equipment will be used.
2. Provisions shall be made to prevent the rated voltage from being exceeded by transient disturbances of more than 140 %.

(18) **Essential Health and Safety Requirements**

Covered by the standards listed at item (9).

(19) **Test documentation**

As listed in Report No. 219865100, Issue 1.

(20) **Certificate history**

Issue 0 - 219865100 Initial certificate  
Issue 1 - 222549600 Addition of temperature range parameter "C"