

CERTIFICATE

(1) Type Examination

(2) **Product intended for use in potentially explosive atmospheres - Directive 2014/34/EU**

(3) Type Examination Certificate Number: **DEKRA 15ATEX0017 X** Issue Number: **3**

(4) Product: **Industrial Ethernet Rail Switch Power Series RSP**

(5) Manufacturer: **Hirschmann Automation and Control GmbH**

(6) Address: **Stuttgarter Strasse 45-51, 72654 Neckartenzlingen, Germany**

(7) This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

(8) DEKRA Certification B.V., certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014.

The examination and test results are recorded in confidential test report no. NL/DEK/ExTR15.0026/02.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0 : 2018 EN 60079-7 : 2015 + A1 : 2018 EN 60079-15 : 2019

except in respect of those requirements listed at item 18 of the Schedule.

(10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.

(11) This Type Examination Certificate relates only to the design and construction of the specified product and not to the manufacturing process and its monitoring.

(12) The marking of the product shall include the following:



II 3 G Ex ec nC IIC T4 Gc

Date of certification: **30 August 2021**

DEKRA Certification B.V.

A handwritten signature in blue ink, appearing to read 'R. Schuller'.

R. Schuller
Certification Manager

(13) **SCHEDULE**

(14) **to Type Examination Certificate DEKRA 15ATEX0017 X**

Issue No. 3

(15) **Description**

Industrial Ethernet Rail Switch Power Series RSP.

The rail mounted modules are intended for use in industrial automation applications, communicate via electrical or optical interfaces and differ with regard to the number of interfaces and the media type for connecting segments.

Ambient temperature range: 0 °C to +60 °C for Temperature range parameter "S"
-40 °C to +70 °C for Temperature range parameters "T" and "E"

See Annex 1 to NL/DEK/ExTR15.0026/02 for type designation.

Electrical data

Supply: 24 ... 48 Vdc, 1,0 A ... 0,4 A for voltage range parameter "CC"

Relay output: max. 60 Vdc / 30 Vac, max. 1 A (resistive load)

Installation instructions

The instructions provided with the product shall be followed in detail to assure safe operation.

(16) **Report Number**

No. NL/DEK/ExTR15.0026/02.

(17) **Specific conditions of use**

1. The equipment shall only be used in an area of not more than pollution degree 2, as defined in EN 60664-1.
2. The modules shall be installed in a suitable enclosure providing a degree of protection of at least IP54 according to EN IEC 60079-0, taking into account the environmental conditions under which the equipment will be used.
3. Provisions shall be made to prevent the rated voltage from being exceeded by transient disturbances of more than 119 V.

(18) **Essential Health and Safety Requirements**

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item (9), the listed product series is also in compliance with EN 60079-15 : 2010, as detailed in the report.

(19) **Test documentation**

As listed in Report No. NL/DEK/ExTR15.0026/02.