

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Network and Communication Components

with type designation(s)

Greyhound Switch GRS1020/1120/1030/1130, Greyhound Media Modules GRM20

Issued to

Hirschmann Automation and Control GmbH
Neckartenzlingen, Baden-Württemberg, Germany

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Location classes:

Temperature D*

Humidity B

Vibration A

EMC B

Enclosure A

***see Application/Limitation**

This Certificate is valid until **2021-12-11**.

Issued at **Hamburg** on **2019-10-04**

DNV GL local station: **Augsburg**

Approval Engineer: **Heinz Scheffler**



for **DNV GL**
Digitally Signed By:
Papanuskas, Joannis

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-020854-3**
Certificate No: **TAA00000XJ**
Revision No: **2**

Product description

The device name corresponds to the product code. The product code is made up of characteristics with defined positions. The characteristic values stand for specific product properties.

GREYHOUND Switch

Item	Characteristic	Characteristic value	Description
1..3	Product	GRS	Greyhound Switch
4	Series	1	Greyhound Series
5	Port position	0 1	Ports front, power supply rear Ports rear, power supply rear
6	Data rate	2 3	FE-Switch FE-Switch with GE-Uplink Ports
7	PoE support	0	No PoE support
8	Hypen	-	
9...12	Configuration fixed ports	16T9 8T8Z	16 x Fast Ethernet TX ports 8xFE TX ports + 8xFE SFP ports
13	Operating temperature range	S C T E	0°C ... +60°C 0°C ... +60°C, conformal coating -40°C ... +70°C -40°C ... +70°C, conformal coating
14	Power supply unit 1	C M	Rated voltage: 24 ... 48 VDC Voltage range incl. maximum tolerances: 18...60 V DC Rated voltage: 110...230 V AC, 50...60Hz Voltage range incl. maximum tolerances: 88...265 V AC, 47...63 Hz
15	Power supply unit 2	C M 9	Rated voltage: 24 ... 48 VDC Voltage range incl. maximum tolerances: 18...60 V DC Rated voltage: 110...230 V AC, 50...60Hz Voltage range incl. maximum tolerances: 88...265 V AC, 47...63 Hz no second power supply
16...17	Approvals		Not relevant for this certificate
18...19	Customization	HH	Hirschmann Standard
20	Hardware configuration	S	Standard
21	Software configuration	E	Standard
22...23	Software level	2S	HiOS Layer 2 Standard
24...28	Software version	04.x 05.x 06.x 07.x 08.x	HiOS 04.x HiOS 05.x HiOS 06.x HiOS 07.x HiOS 08.x
29...30	Maintenance version	00	Maintance version 00

Job Id: **262.1-020854-3**
Certificate No: **TAA00000XJ**
Revision No: **2**

GREYHOUND Switch Media Module

Item	Characteristic	Characteristic value	Description
1..3	Product	GRM	Greyhound Switch Media Module
4	Data rate	2	10/100 Mbit/s Ports
5	PoE support	0	No PoE support
6	Hypen	-	
7...8	Configuration ports 1+3	TT ZZ MM NN VV UU	2 x TP TX, RJ45, 100 Mbit/s 2 x SFP Slot, 100 Mbit/s 2 x MM FX, DSC, 100 Mbit/s 2 x MM FX, ST, 100 Mbit/s 2 x SM FX, DSC, 100 Mbit/s 2 x SM FX, ST, 100 Mbit/s
9...10	Configuration ports 5+7	TT ZZ MM NN VV UU	2 x TP TX, RJ45, 100 Mbit/s 2 x SFP Slot, 100 Mbit/s 2 x MM FX, DSC, 100 Mbit/s 2 x MM FX, ST, 100 Mbit/s 2 x SM FX, DSC, 100 Mbit/s 2 x SM FX, ST, 100 Mbit/s
11...12	Configuration ports 2+4	TT ZZ MM NN VV UU	2 x TP TX, RJ45, 100 Mbit/s 2 x SFP Slot, 100 Mbit/s 2 x MM FX, DSC, 100 Mbit/s 2 x MM FX, ST, 100 Mbit/s 2 x SM FX, DSC, 100 Mbit/s 2 x SM FX, ST, 100 Mbit/s
13...14	Configuration ports 6+8	TT ZZ MM NN VV UU	2 x TP TX, RJ45, 100 Mbit/s 2 x SFP Slot, 100 Mbit/s 2 x MM FX, DSC, 100 Mbit/s 2 x MM FX, ST, 100 Mbit/s 2 x SM FX, DSC, 100 Mbit/s 2 x SM FX, ST, 100 Mbit/s
15	Operating temperature range	S C T E	0°C ... +60°C 0°C ... +60°C, conformal coating -40°C ... +70°C -40°C ... +70°C, conformal coating
16...17	Approvals		Not relevant for this certificate
18...19	Customization	HH	Hirschmann Standard
20	Hardware configuration	S	Standard
21	Software configuration	E	Standard
22...23	Software level	2S	HiOS Layer 2 Standard
24...28	Software version	04.x 05.x 06.x 07.x 08.x	HiOS 04.x HiOS 05.x HiOS 06.x HiOS 07.x HiOS 08.x

Application/Limitation

Location class Temperature D: -40°C / 16h

Equipment for installation outside a distance of 5 m from a standard or a steering magnetic compass.
The installation requirements according to the User Manual's Installation are to be observed. Equipment for installation outside a distance of 5 m from a standard or a steering magnetic compass.

Job Id: **262.1-020854-3**
Certificate No: **TAA00000XJ**
Revision No: **2**

Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNVGL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNVGL Rules for Ships Pt.4 Ch.9 Control and Monitoring Systems.

If the control system is intended for remote software maintenance the functionality shall be part of the system documentation as required in DNV GL Rules for Ships Pt.4 Ch.9 Control and Monitoring Systems.

Product certificate

If specified in the Rules, ref. Pt.4 Ch.9 Sec.1, the control and monitoring system in which the above listed hardware is used shall be delivered with a product certificate. For each such delivery the certification test is to be performed at the manufacturer of the application system before the system is shipped to the yard. The test shall be done according to an approved test program. After the certification the clause for application software control will be put into force.

Clause for application software control

All changes in software are to be recorded as long as the system is in use on board. The records of all changes are to be forwarded to DNVGL for evaluation and approval. Major changes in the software are to be approved before being installed in the computer.

Type Approval documentation

See ANNEX

Place of Production

See ANNEX

Tests carried out

Applicable tests according to Class Guideline DNVGL-CG-0339, Edition November 2015.

Marking of product

The products to be marked with:

- device name
- manufacturer name
- serial number.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE